



RECOMMENDED  
CABLE STRIPPING DIM'S  
(建議剝線尺寸)

PANEL DIMENSIONS

百展科技有限公司			
TITLE CABLE ASS'Y(SMA REVERSE JACK WITH 1.37 CABLE)			
DRAWING NO.	CAB39FPXM01.37F	REV	0
CUSTOMER NO.	IPEX-RSMA(F)1.37-40	REV	

DIMENSIONS ARE IN MILLIMETERS	
UNLESS OTHERWISE SPECIFIED TOLERANCES	
ANGLES	= ±3°
UP TO 6	= ±0.12
6-40	= ±0.2
40-120	= ±0.6
120-315	= ±1
ABOVE 315	= ±1.6
CUSTOMER CODE	306
SCALE	3/1

APPROVED	<i>Bob</i>	DATE	11-01-11'
CHECKED	<i>Annie</i>	DATE	11-01-11'
DRAWN	<i>Annie</i>	DATE	11-01-11'
FILE NO.	D:\LI-YUNG\CAB\CAB09FPXM004F-0		

5	保護套				
4	HEAT SHRINK TUBING (ø2.5)		BLACK	1	HT00AAA001F L=15
3	I-PEX			1	CAB000PXM0132F
2	1.37 CABLE		BLACK	1	
1	CONNECTOR	BRASS	GOLD/F	1	396111AX11055F
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.