



RECOMMENDED
CABLE STRIPPING DIM'S
(建議剝線尺寸)

			DIMENSIONS ARE IN MILLIMETERS		APPROVED <i>Bob</i> DATE 12-07-11'	
			UNLESS OTHERWISE SPECIFIED TOLERANCES		CHECKED <i>Bob</i> DATE 12-07-11'	
TITLE CABLE ASS'Y (N STR PLUG TO N STR PLUG WITH CFD-400)			ANGLES = $\pm 3^\circ$		DRAWN <i>Bob</i> DATE 12-07-11'	
			UP TO 6 = ± 0.12			
DRAWING NO. CAB05M05M400F1			6-40 = ± 0.2		FILE NO. D:\LI-YUNG\	
REV 0			40-120 = ± 0.6			
CUSTOMER NO.			120-315 = ± 1		NO. DESCRIPTION MATERIAL FINISH Q'TY DRAWING NO.	
REV			ABOVE 315 = ± 1.6			
			CUSTOMER CODE		3 HEAT SHRINK TUBING ($\phi 13$) BLACK 2 203-3213-00010 L=30	
			SCALE 1/1		2 LMR-400 BLACK 1 813-1101-40092	
					1 CONNECTOR BRASS NICKEL 2 051111AB40015F	

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
3	HEAT SHRINK TUBING ($\phi 13$)		BLACK	2	203-3213-00010 L=30
2	LMR-400		BLACK	1	813-1101-40092
1	CONNECTOR	BRASS	NICKEL	2	051111AB40015F